



Pattern: GLR15

Description:

The GLR15 MPT tyre which is specially designed for multi-purpose vehicles and wheel loaders.

This tyre features good traction and self cleaning properties.

TECHNICAL DATA:

Size	Pattern	Load Index	Speed Symbol	Type	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (kPa)	Load Capacity		Tread Depth (mm)
									(km/h)	(kgs)	
18"											
335 / 80 R 18	GLR15	134/*145	B/*A2	TL	11.00	988	325	380	50/*10	2120/*2900	18.00
405 / 70 R 18	GLR15	141/*153	B/*A2	TL	11.00	1020	400	380	50/*10	2575/*3650	20.00
20"											
335 / 80 R 20	GLR15	136/*147	B/*A2	TL	11.00	1030	315	380	50/*10	2240/*3075	19.00
365 / 80 R 20	GLR15	141/*153	B/*A2	TL	13.00	1085	345	380	50/*10	2575/*3650	21.00
405 / 70 R 20	GLR15	143/*155	B/*A2	TL	13.00	1090	400	380	50/*10	2725/*3875	20.00
24"											
405 / 70 R 24	GLR15	146/*158	B/*A2	TL	13.00	1170	400	380	50/*10	2725/*3000	20.00

Legal Information:

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Guizhou Tyre Co., LTD. or any subsidiary or affiliated company does not undertake any responsibility or liability for undetected errors and/or misprints.

All rights reserved. The materials and contents of this publication are the exclusive property of Guizhou Tyre Co., LTD. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish any contents in whole or in part on paper format and electronic format or otherwise without prior written consent by Guizhou Tyre Co., LTD.