



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **D**

The high speed rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

Tractor R-1 - 210/95R16

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
								Speed							
								Tractor application							
		SW mm	OD mm					Static Kmph	10 Kmph	25 Kmph	30 Kmph	40 Kmph	50 Kmph	65 Kmph	70 Kmph
210/95R16	W7X16, W6X16	214	806	363	2381	106D	0.8	1035	675	533	518	493	473	450	410
							1.2	1334	870	687	667	635	609	580	528
							1.6	1633	1065	841	817	777	746	710	646
							2	1955	1275	1007	978	931	893	850	774
							2.4	2185	1425	1126	1093	1040	998	950	865

