



# RADIAL MEDIUM TRUCK TIRES LINE HAUL SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G395® LHS™ Featuring Fuel Max® Technology</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	40.2	1,022	18.8	478	517	321	18.0	12.9	328	75
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	117	53	8.25	10.8	274	41.2	1,047	19.2	488	504	313	18.0	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	119	54	8.25	11.1	282	41.3	1,050	19.4	493	503	312	18.0	12.5	318	75
<b>G305™ LHD™ Featuring Fuel Max® Technology</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	121	55	8.25	11.1	282	41.1	1,044	19.2	488	508	315	26.0	12.9	328	75
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	125	57	8.25	10.9	277	41.9	1,065	19.5	496	498	309	26.0	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	126	57	8.25	10.8	274	42.3	1,075	19.8	503	493	306	26.0	12.5	318	75
<b>G316™ LHS™ Featuring Fuel Max® Technology</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	102	46	8.25	11.1	282	39.8	1,011	18.6	473	518	322	12.0	12.9	328	75
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	106	48	8.25	10.9	277	41.0	1,042	19.0	483	503	312	12.0	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	108	49	8.25	11.1	282	41.0	1,042	19.1	485	503	312	12.0	12.5	318	75
<b>G395® LHS™</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	117	53	8.25	10.8	274	41.2	1,047	19.2	488	504	313	18.0	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	121	55	8.25	10.8	274	41.2	1,047	19.2	488	504	313	18.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	125	57	8.25	10.8	274	43.2	1,098	20.1	511	481	299	18.0	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	129	59	8.25	10.8	274	43.2	1,098	20.1	511	481	299	18.0	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	40.2	1,022	18.8	478	517	321	18.0	12.9	328	75
295/75R22.5	H	6,610	3,000	120	760	6,005	2,725	110	760	116	52	8.25	11.1	282	40.2	1,022	18.8	478	517	321	18.0	12.0	305	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	120	54	8.25	11.1	282	41.3	1,050	19.4	493	503	312	18.0	12.5	318	75
<b>G372A LHD™</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	129	59	8.25	10.9	277	42.3	1,075	19.7	501	494	307	30.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	138	63	8.25	11.0	280	44.3	1,126	20.6	523	471	292	30.0	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	128	58	8.25	11.1	282	41.1	1,044	19.2	488	508	315	30.0	12.9	328	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	132	60	8.25	11.1	282	42.3	1,075	19.8	503	494	307	30.0	12.5	318	75
<b>G362™</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	132	60	8.25	10.9	277	42.0	1,067	19.8	503	497	309	28.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	140	64	8.25	10.9	277	44.0	1,118	20.8	529	474	294	28.0	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	126	57	8.25	11.1	282	42.0	1,067	19.7	501	497	309	28.0	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	123	56	8.25	11.1	282	40.8	1,037	19.1	485	512	318	28.0	12.9	328	75



## RADIAL MEDIUM TRUCK TIRES HIGHWAY SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G338 1AD®</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	134	61	8.25	11.1	282	42.1	1,070	19.8	503	496	308	30.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	143	65	8.25	11.1	282	44.1	1,121	20.7	526	473	294	30.0	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	124	56	8.25	11.1	282	41.0	1,042	19.1	485	509	316	30.0	12.9	328	75
<b>G314™</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	109	49	8.25	10.8	274	41.1	1,044	19.3	490	502	312	12.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	116	53	8.25	10.8	274	43.1	1,095	20.3	516	478	297	12.0	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	97	44	8.25	11.1	282	39.8	1,011	18.6	473	518	322	12.0	12.9	328	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	107	48	8.25	11.1	282	40.9	1,039	19.2	488	504	313	12.0	12.5	318	75
<b>Marathon® LHT™</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
245/70R17.5#	H	6,005	2,725	130	900	6,175	2,800	130	900	78	35	7.50	10.1	257	31.3	795	14.4	366	659	409	16.0	11.0	280	65
<b>G104™ RST®</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	87	40	7.50	10.0	254	36.4	925	17.0	432	568	353	13.0	11.3	287	81
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	100	45	7.50	10.3	262	37.5	953	17.4	442	550	342	14.0	11.9	302	75
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
10.00R15TR#	G	5,070	2,300	105	720	4,805	2,180	105	720	96	44	7.50	10.7	272	36.4	925	17.0	432	566	351	14.0	12.5	318	68
11R17.5HC#	H	5,675	2,575	120	830	5,355	2,430	120	830	99	45	8.25	10.7	272	36.4	925	17.0	432	566	351	14.0	12.5	318	68

#Imported.





# RADIAL MEDIUM TRUCK TIRES REGIONAL PICK-UP AND DELIVERY SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G149 RSA®</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
9R22.5	F	4,540	2,060	105	720	4,300	1,950	105	720	93	42	6.75	9.0	229	38.4	977	18.1	460	541	336	18.0	10.3	262	75
10R22.5	F	5,205	2,360	100	690	4,940	2,240	100	690	106	48	7.50	10.2	259	40.1	1,020	18.9	481	518	322	20.0	11.4	290	75
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	111	50	7.50	10.2	259	40.1	1,020	18.9	481	518	322	20.0	11.4	290	75
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	121	55	8.25	10.9	277	41.6	1,058	19.4	493	501	311	20.0	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	126	57	8.25	10.9	277	41.6	1,058	19.4	493	501	311	20.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	130	59	8.25	11.0	280	43.6	1,109	20.3	516	476	296	20.0	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	134	61	8.25	11.0	280	43.6	1,109	20.3	516	476	296	20.0	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	143	65	9.00	11.6	295	43.0	1,094	20.1	511	483	300	21.0	13.5	343	75
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	62	28	6.75	8.9	226	32.2	819	15.0	382	640	397	15.5	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	72	32	7.50	9.6	244	33.2	845	15.5	394	626	389	16.5	11.0	280	75
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	89	40	7.50	9.2	234	37.1	944	17.5	445	560	348	19.0	11.0	280	75
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	100	690	101	46	7.50	10.1	257	38.5	979	18.2	463	540	335	19.0	11.6	295	75
<b>TUBELESS TIRES ON 5" DROP CENTERS</b>																								
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	52	23	6.00	8.7	221	30.5	776	14.3	364	680	422	14.5	9.9	252	75
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	50	22	6.00	8.8	224	29.5	750	13.8	351	699	434	14.5	10.2	259	75
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	56	25	6.50	9.5	242	31.0	789	14.4	366	666	414	15.5	10.8	275	75
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	56	25	6.50	9.5	242	31.0	789	14.4	366	666	414	15.5	10.8	275	75
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
9.00R20	F	5,205	2,360	100	690	4,940	2,240	100	690	109	49	7.00	10.2	259	40.1	1,020	18.9	481	518	322	20.0	11.6	295	75
10.00R20	G	6,175	2,800	105	720	5,840	2,650	105	720	121	55	7.50	10.9	277	41.6	1,058	19.4	493	500	311	20.0	11.4	290	75
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	144	65	8.00	11.6	295	43.0	1,094	20.1	511	483	300	21.0	13.2	336	75
<b>G169 RSA®</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	92	42	7.50	10.0	254	36.7	934	17.1	435	566	351	18.0	11.3	287	81
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	103	47	7.50	10.4	265	37.7	959	17.6	448	551	342	18.0	11.9	303	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	116	52	8.25	11.1	282	40.5	1,030	18.9	481	513	319	20.0	12.9	328	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	120	54	8.25	11.1	282	41.6	1,058	19.5	496	499	310	20.0	12.5	318	75
<b>G291™</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
315/80R22.5	J	8,270	3,750	120	830	7,610	3,450	120	830	142	64	9.00	12.4	315	42.3	1,076	19.7	501	491	305	18.0	13.8	351	75
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	142	64	9.00	12.4	315	42.3	1,076	19.7	501	491	305	18.0	13.8	351	68



# RADIAL MEDIUM TRUCK TIRES REGIONAL PICK-UP AND DELIVERY SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G647 RSS®</b>																								
<b>TUBELESS TIRES ON 5" DROP CENTERS</b>																								
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	52	24	6.00	8.6	219	30.5	776	14.2	361	676	420	14.5	9.9	252	75
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	51	23	6.00	8.7	221	29.4	748	13.7	348	701	435	14.5	10.2	259	75
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	57	26	6.50	9.6	244	30.9	786	14.4	366	667	414	15.5	10.8	275	75
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	57	26	6.50	9.6	244	30.9	786	14.4	366	667	414	15.5	10.8	275	75
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	60	27	6.00	8.3	211	33.3	847	15.6	397	619	384	13.5	9.3	237	75
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	63	28	6.75	8.9	226	32.2	819	15.0	382	640	397	16.5	10.0	254	75
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	65	29	6.75	8.9	226	32.2	819	15.0	382	640	397	16.5	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	75	34	7.50	9.5	242	33.2	845	15.4	392	626	389	16.5	11.0	280	75
245/70R19.5	F	4,080	1,850	95	660	3,970	1,800	95	660	71	32	7.50	9.5	242	33.2	845	15.4	392	626	389	16.5	11.0	280	75
<b>G159™ A</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
265/70R19.5	G	5,355	2,430	120	830	5,070	2,300	120	830	82	37	7.50	10.3	262	34.0	865	15.9	404	606	376	16.0	11.6	295	75
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
8.75R16.5LT	E	2,680	1,215	80	550	2,405	1,090	80	550	48	22	6.75	8.7	221	28.9	735	13.6	346	719	446	15.0	9.9	252	75
365/80R20#	J	10,000	4,535	130	900	N/A	N/A	N/A	N/A	177	80	10.00	14.4	366	43.0	1,094	19.8	504	483	300	20.0	N/A	N/A	68
<b>TUBELESS TIRES ON 5" DROP CENTERS</b>																								
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.6	244	30.7	781	14.3	364	671	417	15.0	10.8	275	75
<b>G182 RSD®</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	134	60	8.25	10.8	275	42.1	1,071	19.6	499	496	308	28.0	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	136	61	8.25	10.8	275	42.1	1,071	19.6	499	496	308	28.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	143	65	8.25	11.0	280	44.1	1,122	20.8	529	473	294	28.0	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	145	65	8.25	11.0	280	44.1	1,122	20.8	529	473	294	28.0	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	121	55	8.25	11.3	287	40.8	1,038	19.0	483	512	318	28.0	12.9	328	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	126	57	8.25	11.2	285	42.0	1,068	19.5	496	497	309	28.0	12.5	318	75
<b>G622 RSD™</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	63	28	6.75	8.9	226	32.4	824	15.1	384	641	398	19.0	10.0	254	75
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	65	29	6.75	8.9	226	32.4	824	15.1	384	641	398	19.0	10.0	254	75
245/70R19.5	F	4,080	1,850	95	660	3,970	1,800	95	660	71	32	6.75	9.6	244	33.5	852	15.6	397	620	385	19.0	11.0	280	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	75	34	6.75	9.7	245	33.5	852	15.6	397	620	385	19.0	11.0	280	75

‡Imported.





## RADIAL MEDIUM TRUCK TIRES REGIONAL PICK-UP AND DELIVERY SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G164 RTD®</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	128	58	8.25	11.0	280	42.0	1,068	19.5	496	497	309	24.0	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	132	59	8.25	11.0	280	42.0	1,068	19.5	496	497	309	24.0	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	137	62	8.25	10.8	275	43.8	1,114	20.6	524	477	296	24.0	12.5	318	75
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	120	54	8.25	11.1	282	41.7	1,061	19.7	501	501	311	24.0	12.5	318	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	116	52	8.25	11.1	282	40.5	1,030	19.1	486	515	320	24.0	12.9	328	75
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	95	43	7.50	9.9	252	36.9	939	17.2	438	563	350	22.0	11.3	287	81
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
10.00R20	G	6,175	2,650	105	720	5,840	2,650	105	720	127	57	7.50	10.6	270	41.8	1,063	19.6	499	499	310	24.0	12.5	318	75
<b>G133™ LT</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	51	23	6.00	8.5	216	30.4	773	14.3	364	683	424	15.0	9.9	252	75
LT225/75R16	E	2,680	1,215	80	550	2,470	1,120	80	550	48	22	6.00	8.7	221	29.4	748	13.7	348	701	435	15.0	10.2	259	75
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.4	239	30.9	786	14.4	366	667	414	15.0	10.8	275	75
LT245/75R16	E	3,042	1,380	80	550	2,778	1,260	80	550	55	25	6.50	9.4	239	30.9	786	14.4	366	667	414	15.0	10.8	275	75
<b>G124™ LT</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	63	28	6.75	8.9	226	32.4	824	15.1	384	641	398	19.0	10.0	254	75
245/70R19.5	F	4,080	1,850	85	590	3,970	1,800	85	590	72	32	7.50	10.2	259	33.2	845	15.5	394	626	389	20.0	11.0	280	75
245/70R19.5	G	4,540	2,060	100	690	4,410	2,000	100	690	76	34	7.50	10.2	259	33.2	845	15.5	394	626	389	20.0	11.0	280	75
265/70R19.5	G	5,355	2,430	120	830	5,070	2,300	120	830	86	39	7.50	10.3	262	34.3	872	16.0	407	606	376	19.0	11.6	295	75
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	93	42	7.50	9.5	242	37.3	949	17.4	443	557	346	20.0	11.0	280	75
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	100	690	104	47	7.50	9.9	252	38.7	984	18.2	463	537	333	21.0	11.6	295	75
9R22.5	F	4,540	2,060	105	720	4,300	1,950	105	720	94	42	6.75	9.0	229	38.6	982	18.1	460	538	334	20.0	10.3	262	75
10R22.5	F	5,205	2,360	100	690	4,940	2,240	100	690	106	48	7.50	10.0	254	40.3	1,025	19.0	483	514	319	21.0	11.4	290	75
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	111	50	7.50	10.0	254	40.3	1,025	19.0	483	514	319	21.0	11.4	290	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	146	66	9.00	11.2	285	43.1	1,096	20.2	514	482	299	22.0	13.5	343	75
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
9.00R20	F	5,205	2,360	100	690	4,940	2,240	100	690	109	49	7.00	10.0	254	40.3	1,025	18.7	476	517	321	21.0	11.6	295	75
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	146	66	8.00	11.4	290	43.1	1,096	20.2	514	482	299	22.0	13.2	336	75
<b>REGIONAL RHD®</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
315/80R22.5#	J	8,820	4,000	125	850	7,390	3,350	125	850	163	74	9.00	12.4	315	43.0	1,094	19.9	506	485	301	27.0	13.8	351	75
12R22.5#	J	7,830	3,550	125	850	6,940	3,150	125	850	135	61	8.25	11.7	298	43.1	1,096	20.2	514	484	301	27.0	13.0	331	75

#Imported.



## RADIAL MEDIUM TRUCK TIRES MIXED SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G670 RV®</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	59	27	6.75	8.9	226	32.0	814	14.9	379	644	400	13.0	10.0	254	75
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	142	64	9.00	12.5	318	42.5	1,081	19.8	504	489	304	16.5	13.8	351	75
245/70R19.5	F	4,080	1,850	95	660	3,970	1,800	95	660	65	29	7.50	9.7	247	33.0	839	15.3	389	626	389	13.5	11.0	280	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	70	32	7.50	9.7	247	33.0	839	15.3	389	626	389	13.5	11.0	280	75
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	89	40	7.50	10.0	254	36.4	926	17.0	432	566	351	14.5	11.3	287	75
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	96	44	7.50	10.4	265	37.6	956	17.4	443	548	340	14.5	11.9	303	75
275/80R22.5	H	7,160	3,250	125	860	6,610	3,000	125	860	114	51	8.25	11.1	282	40.2	1,023	18.8	478	517	321	18.0	12.3	313	75
295/80R22.5	H	7,830	3,550	125	860	6,940	3,150	125	860	110	50	9.00	12.1	308	41.3	1,051	19.2	488	499	310	16.0	13.2	336	75





# RADIAL MEDIUM TRUCK TIRES MIXED SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
<b>G287 MSA® Featuring DuraSeal Technology®</b>																									
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																									
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	160	72	9.00	12.4	315	42.8	1,089	19.8	504	485	301	23.0	13.8	351	68	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	146	66	8.25	11.0	280	41.7	1,061	19.5	496	498	309	22.0	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	156	70	8.25	11.0	280	43.7	1,112	20.4	519	475	295	22.0	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	160	72	9.00	11.7	298	43.1	1,096	20.2	514	482	299	22.0	13.5	343	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	171	77	8.25	11.3	287	44.9	1,142	21.1	537	463	288	22.0	13.5	343	68	
<b>G287® HSS® Featuring DuraSeal Technology®</b>																									
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																									
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	156	71	9.00	12.4	315	42.8	1,089	19.8	504	485	301	23.0	13.8	351	62	
<b>G288 MSA® Featuring DuraSeal Technology™</b>																									
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	145	65	8.25	11.1	282	41.9	1,066	19.7	501	498	309	25.0	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	154	70	8.25	11.1	282	44.0	1,119	20.7	527	474	294	25.0	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	151	68	9.00	11.7	298	43.3	1,101	20.2	514	482	299	25.0	13.5	343	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	163	74	8.25	11.3	287	45.0	1,145	21.0	534	464	288	25.0	13.5	343	68	
<b>G177™ Featuring DuraSeal Technology®</b>																									
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	154	69	8.25	10.9	277	42.3	1,076	19.7	501	493	306	32.0	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	163	74	8.25	10.9	277	44.3	1,127	20.7	527	471	292	32.0	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	169	76	9.00	11.5	293	43.7	1,112	20.5	521	478	297	32.0	13.5	343	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	181	82	9.00	11.5	293	45.7	1,162	21.5	547	457	284	33.0	13.5	343	68	
<b>G287 MSA®</b>																									
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																									
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	147	66	8.25	11.0	280	43.7	1,112	20.4	519	475	295	22.0	12.5	318	68	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	138	62	8.25	11.0	280	41.7	1,061	19.5	496	498	309	22.0	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	151	68	9.00	11.7	298	43.1	1,096	20.2	514	482	299	22.0	13.5	343	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	162	73	8.25	11.3	287	44.9	1,142	21.1	537	463	288	22.0	13.5	343	68	
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	156	71	9.00	12.4	315	42.8	1,089	19.8	504	485	301	23.0	13.8	351	68	
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																									
10.00R20	H	6,610	3,000	120	830	6,005	2,725	120	720	133	60	7.50	10.6	270	41.8	1,063	19.5	496	497	309	22.0	12.5	318	68	
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	152	69	8.00	11.5	293	43.1	1,096	20.2	514	482	299	22.0	13.2	336	68	
11.00R22	H	7,830	3,550	120	830	7,160	3,250	120	830	162	73	8.00	11.3	287	45.0	1,145	21.0	534	462	287	22.0	13.2	336	68	



# RADIAL MEDIUM TRUCK TIRES MIXED SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G287 HSS™</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	156	71	9.00	12.4	315	42.8	1,089	19.8	504	485	301	23.0	13.8	351	62
<b>G288 MSA®</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	146	66	8.25	11.1	282	44.0	1,119	20.7	527	474	294	25.0	12.5	318	68
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	137	62	8.25	11.1	282	41.9	1,066	19.7	501	498	309	25.0	12.5	318	68
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	151	68	9.00	11.7	298	43.3	1,101	20.2	514	482	299	25.0	13.5	343	68
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	163	74	8.25	11.3	287	45.0	1,145	21.0	534	464	288	25.0	13.5	343	68
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	95	43	7.50	10.0	254	36.9	939	17.3	440	563	350	22.0	11.3	287	68
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	110	50	7.50	10.5	267	37.9	964	17.7	450	548	340	23.0	12.2	310	68
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
10.00R20	H	6,610	3,000	120	830	6,005	2,725	120	720	132	59	7.50	10.8	275	41.8	1,063	19.5	496	499	310	25.0	12.5	318	68
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	154	69	8.00	11.5	293	43.1	1,096	20.1	511	483	300	25.0	13.2	336	68
11.00R22	H	7,830	3,550	120	830	7,160	3,250	120	830	164	74	8.00	11.5	293	45.1	1,147	21.2	539	463	288	25.0	13.2	336	68
12.00R24	J	9,370	4,250	120	830	8,540	3,875	120	830	189	85	8.50	11.9	303	48.5	1,234	22.5	572	430	267	25.0	14.1	359	62
<b>G286™</b>																								
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
11.00R22	H	7,830	3,550	120	830	7,160	3,250	120	830	161	73	8.00	11.4	290	45.0	1,145	21.0	534	462	287	23.0	13.2	336	68
11.00R24	H	8,270	3,750	120	830	7,610	3,450	120	830	167	75	8.00	11.4	290	47.0	1,196	22.0	560	442	274	23.0	13.2	336	68
14.00R20	L	11,000	5,000	115	790	10,200	4,625	115	790	236	106	10.00	15.0	382	48.4	1,231	22.2	565	431	268	19.0	17.7	450	55
<b>G286A™ SS</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
385/65R22.5	J	9,370	4,250	120	830	N/A	N/A	N/A	N/A	176	79	11.75	14.9	379	42.4	1,079	19.5	496	490	304	19.0	N/A	N/A	68
425/65R22.5	L	11,400	5,150	120	830	N/A	N/A	N/A	N/A	201	91	12.25	16.1	410	44.2	1,124	20.3	516	470	292	20.0	N/A	N/A	68
445/65R22.5	L	12,300	5,600	120	830	N/A	N/A	N/A	N/A	226	102	13.00	17.3	440	45.6	1,160	20.8	529	456	283	21.0	N/A	N/A	62
<b>G244 MSD®</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	142	64	8.25	10.9	277	42.0	1,068	19.8	504	497	309	28.0	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	151	68	8.25	10.9	277	44.0	1,119	20.8	529	474	294	28.0	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	156	70	9.00	11.4	290	43.5	1,107	20.4	519	480	298	29.0	13.5	343	68
<b>G178™ SS</b>																								
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																								
385/65R22.5	J	9,370	4,250	120	830	N/A	N/A	N/A	N/A	180	81	11.75	14.9	379	43.0	1,094	19.8	504	485	301	28.0	N/A	N/A	68
425/65R22.5	L	11,400	5,150	120	830	N/A	N/A	N/A	N/A	210	95	12.25	16.1	410	44.9	1,142	20.7	527	465	289	29.0	N/A	N/A	68
445/65R22.5	L	12,300	5,600	120	830	N/A	N/A	N/A	N/A	231	104	13.00	17.3	440	46.2	1,175	21.1	537	452	281	30.0	N/A	N/A	62







## RADIAL MEDIUM TRUCK TIRES MIXED SERVICE

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in				mm		
<b>G177™</b>																									
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	146	66	8.25	10.9	277	42.3	1,076	19.7	501	493	306	32.0	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	155	70	8.25	10.9	277	44.3	1,127	20.7	527	471	292	32.0	12.5	318	68	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	160	72	9.00	11.5	293	43.7	1,112	20.5	521	478	297	33.0	13.5	343	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	172	78	9.00	11.5	293	45.7	1,162	21.5	547	457	284	33.0	13.5	343	68	
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																									
10.00R20	H	6,610	3,000	120	830	6,005	2,725	120	720	139	63	7.50	11.0	280	42.3	1,076	19.7	501	493	306	32.0	12.5	318	68	
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	161	73	8.00	11.4	290	43.7	1,112	20.5	521	478	297	33.0	13.2	336	68	
11.00R22	H	7,830	3,550	120	830	7,160	3,250	120	830	172	78	8.00	11.4	290	45.7	1,162	21.5	547	457	284	33.0	13.2	336	68	
12.00R24	J	9,370	4,250	120	830	8,540	3,875	120	830	211	95	8.50	12.0	305	49.4	1,257	23.1	588	423	263	40.0	14.1	359	50	
<b>G171™ LT</b>																									
<b>TUBELESS TIRES ON 5° DROP CENTERS</b>																									
LT215/85R16	E	2,680	1,215	80	550	2,470	1,120	80	550	53	24	6.00	8.5	216	30.8	783	14.4	366	674	419	17.0	9.9	252	75	
LT235/85R16	E	3,042	1,380	80	550	2,778	1,260	80	550	57	26	6.50	9.4	239	31.0	789	14.4	366	670	416	18.0	10.8	275	75	
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																									
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	63	28	6.00	8.1	206	33.5	852	15.8	402	620	385	18.0	9.1	231	75	



## MILITARY TIRES

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G177™</b>																								
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																								
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	160	73	8.00	11.4	290	43.7	1,110	20.5	521	478	297	33.0	13.2	335	68
<b>AT-2A™</b>																								
<b>TUBELESS TIRES ON 5° TAPERED OR TYPE III TUBELESS RIMS</b>																								
14.00R20	J	9,960	4,525	100	700	8,740	3,970	90	620	265	120	10.00	15.2	386	49.2	1,250	22.4	569	427	265	30.0	17.7	450	55
16.00R20	M	14,540	6,600	110	750	N/A	N/A	N/A	N/A	332	151	10.00	17.1	434	52.1	1,323	23.7	602	403	250	33.0	20.2	513	55
16.00R21	M	14,540	6,600	110	750	N/A	N/A	N/A	N/A	336	152	10.00	17.1	434	52.1	1,323	23.7	602	403	250	33.0	20.2	513	55
<b>AT-3A™</b>																								
<b>TUBELESS TIRES ON 5° TAPERED OR TYPE III TUBELESS RIMS</b>																								
16.00R20	M	14,540	6,600	110	750	N/A	N/A	N/A	N/A	342	155	10.00	17.4	442	51.6	1,311	22.8	578	407	253	33.0	20.2	513	55
<b>MV/T™</b>																								
<b>TUBELESS TIRES ON 5° TAPERED OR TYPE III TUBELESS RIMS</b>																								
395/85R20	G	9,370	4,250	95	660	N/A	N/A	N/A	N/A	210	95	10.00	15.4	391	46.6	1,184	21.5	546	446	277	26.0	N/A	N/A	68





## LIMITED AVAILABILITY TIRES

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width			Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in	mm			32nds	in	mm	
<b>G114™</b>																										
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																										
10R17.5#	H	4,675	2,120	115	790	4,410	2,000	115	790	73	33	6.75	9.4	239	33.7	856	15.6	396	612	380	14.0	10.9	277	75		
215/75R17.5	H	4,805	2,180	125	860	4,540	2,060	125	860	62	28	6.75	8.8	224	30.5	775	14.2	361	676	420	16.0	10.0	254	75		
235/75R17.5	H	6,005	2,725	125	875	5,675	2,575	125	875	73	33	6.75	9.2	234	31.8	808	14.5	368	648	402	16.0	10.3	262	62		
9R17.5HC#	H	4,410	2,000	110	760	4,190	1,900	110	760	77	35	6.75	8.9	226	33.3	846	15.4	391	619	384	14.0	10.3	262	75		
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																										
8.25R15TR	G	4,080	1,850	105	720	3,860	1,750	105	720	77	35	6.50	9.2	234	33.3	846	15.5	394	619	384	14.0	10.6	269	75		
<b>G186™</b>																										
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																										
10R22.5	F	5,205	2,360	100	690	4,940	2,240	100	690	108	49	7.50	10.0	254	40.4	1,027	18.9	480	514	319	19.0	11.4	290	75		
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	134	61	8.25	10.9	277	41.8	1,062	19.5	496	497	309	20.0	12.5	318	75		
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	142	64	8.25	10.9	277	43.8	1,113	20.5	521	474	294	20.0	12.5	318	75		
<b>G357™</b>																										
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																										
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	760	130	59	8.25	10.8	274	42.0	1,067	19.7	501	497	309	18.0	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	116	52	8.25	11.0	280	41.3	1,050	19.4	493	503	312	18.0	12.5	318	75		
<b>G386™</b>																										
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																										
13R22.5	J	8,820	4,000	125	850	7,390	3,350	125	850	154	70	9.75	12.7	323	44.4	1,128	20.8	529	468	291	21.0	14.2	361	68		
<b>TUBE TYPE TIRES ON TYPE I, II AND III RIMS</b>																										
12.00R20	J	8,270	3,750	120	830	7,610	3,450	120	830	166	75	8.50	11.7	297	44.0	1,118	20.2	513	472	293	22.0	14.1	358	68		
<b>G302 FED™</b>																										
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																										
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	124	56	8.25	11.1	282	41.2	1,047	19.2	488	507	315	28.0	12.9	328	75		
<b>G328™</b>																										
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																										
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	129	59	8.25	10.8	274	42.1	1,070	19.8	503	496	308	28.0	12.5	318	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	137	62	8.25	10.8	274	44.1	1,121	20.8	529	473	294	28.0	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	124	56	8.25	11.1	282	42.0	1,067	19.7	501	497	309	28.0	12.5	318	75		
<b>G614 RST™</b>																										
<b>TUBELESS TIRES ON 5" DROP CENTERS</b>																										
LT235/65R16	G	3,750	1,700	110	750	3,415	1,550	110	750	58	26	6.50	9.5	241	30.7	780	14.4	366	671	417	12.0	10.8	274	75		
<b>G633 RSD™</b>																										
<b>TUBELESS TIRES ON 15" DROP CENTERS</b>																										
8R19.5	F	3,525	1,600	110	760	3,415	1,550	110	760	61	28	6.00	8.1	206	33.4	849	15.6	396	622	386	16.0	9.1	231	75		

#Imported.



## LIMITED AVAILABILITY TIRES

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>MARATHON® LHS™</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
295/80R22.5#	H	7,830	3,550	125	850	6,940	3,150	125	850	137	62	9.00	11.8	300	41.4	1,052	19.2	488	502	312	18.0	13.2	335	81
315/80R22.5#	J	8,820	4,000	125	850	7,390	3,350	125	850	150	68	9.00	12.5	318	42.8	1,088	19.7	501	485	301	18.0	13.8	351	75
<b>REGIONAL RHS™</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
285/70R19.5#	H	6,610	3,000	130	900	6,175	2,800	130	900	93	42	8.25	11.2	285	35.3	897	16.3	414	588	365	17.0	12.5	318	75
315/80R22.5#	J	8,820	4,000	125	850	7,390	3,350	125	850	142	64	9.00	12.4	315	42.5	1,080	19.7	501	626	389	21.0	13.8	351	75
<b>G143™ - CANADA ONLY</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	141	64	8.25	11.0	280	44.2	1,123	20.7	526	472	293	26.0	12.5	318	68
<b>G443™ - CANADA ONLY</b>																								
<b>TUBELESS TIRES ON 15° DROP CENTERS</b>																								
12R22.5#	J	7,830	3,350	125	850	6,940	3,150	125	850	160	73	11.70	11.7	297	43.2	1,098	20.0	508	483	300	26.0	13.0	330	68

#Imported.

