

DIMENSIONAL TABLES FOR MEDIUM/HEAVY TRUCK TYRES

MULTI-PURPOSE & OFF-ROAD 20"

Tyre size	Load index & speed symbol	PR	Tread pattern	Tyre Dimensions [mm]							Rims	Minimum dual spacing [mm]	Tube	Flap				
				New				Standard										
				Width (#)	Outer diameter	Static radius	Rolling circ. (±1%)	Max. width (#)	Max. outer diameter	Rolling circumf. design								
335/80 R 20 MPT (REPLACES 12.5 R 20)	147 K		PS22 Pista	333	1035	478	3105	354	1076	3132	11 11SDC	--	Tubeless (°) (20"Z 596)	(ZD 20)				
		149 K		PS22 Pista	333	1035	478	3105										
365/80 R 20 MPT (REPLACES 14.5 R 20)	149 K		PS22 Pista	365	1092	502	3276	374	1128	3276	11 11SDC	--	Tubeless (°) (20"Z 750)	(ZD 20)				
		152 K		PS22 Pista	365	1092	502	3276										
14.00 R 20 ML	164/160 G	22	PS22 Pista	389 (§)	1245	567	3797	377	1282	3776	10.0	425	Tubeless (°) (20"Z 810)	(U20-9.0)				

(#) On the underlined rim of the list;

(§) ECE54 standard;

(°) Also for fitment with tube.



PS22 PISTA

ALL POSITION TYRE SUITABLE FOR SPECIAL VEHICLES AVAILABLE BOTH AS 'TUBE TYPE' AND 'TUBELESS'. THE TUBELESS VERSION ALLOWS THE APPLICATION OF 'BEAD LOCK' AND 'RUN FLAT' SYSTEMS.



Goods



F Multipurpose: products designed for vehicles used in demanding off-the-road situations on various types of surface (asphalt, track, muddy or grassy terrain, sand).

Available in both tube and tubeless versions. The tubeless version permits the use of the special "bead lock" and "run flat" systems inside the tyre.

TREAD DESIGN

- Robust blocks, alternating with deep grooves, ensure maximum traction, particularly on soft natural surfaces (grass, mud, etc.) or inconsistent terrain (sand).
- The tough ties between the tread blocks provide excellent protection against tearing and chunking.

PS22 PISTA

SIZE

LOAD INDEX AND SPEED CODE

CLICK ON THE TYRE SIZE TO VIEW THE CORRESPONDING EU LABEL

[14.00R20 TT](#)

L 164/160G

[14.00R20 TT](#)

L 164/160G

[335/80 R20MPT](#)

T 147K

[335/80 R20MPT](#)

T 149K

[365/80 R20MPT](#)

T 152K

[365/80 R20MPT](#)

T 149K

[365/85 R20](#)

164G

[395/85 R20](#)

168G (161J)